

Interface	USB 2.0 high-speed (certified) / with High- and Full-Speed capabilities		
Power Supply	USB bus-powered:	4.4 – 5.25V	
Power Consumption	Suspend Current:	<500uA	
	Operating Current:	max. 100 mA	
Performance	Read:	up to 18 MB/sec.	Write: up to 3.5 MB/sec.
Performance Measurement	Using industry-standard benchmark software on a high-end platform.		
Model Code / Size	EAN Code	Size	Color
	7640111162230	2 Gigabyte	aquamarine
	7640111162247	2 Gigabyte	brown
	7640111162254	2 Gigabyte	pink
	7640111162377	2 Gigabyte	black
	7640111162384	4 Gigabyte	black
Flash Type	Multi Level Cell (MLC) NAND Flash		
Dimensions (LxWxH)	~ 8.7 mm x 3.2 mm x 1.5 mm		
Weight	35 grams		
Operating Systems	Without Driver:	Windows XP Windows 2003 Windows 2000 MAC OS 9 and higher Linux 2.6.x	
	With Driver: *	Windows 98SE	
	*) available at disk2go.com		
LED Indicator	none		
Environmental Conditions	Drop test:	Withstands drops of up to 90cm	
Device in operation	Shock:	max 55 G	
	Temperature:	0 °C to 50 °C	
Device not in operation/Storage	Shock:	max 55 G	
	Temperature:	-20 °C to 70 °C	
Service/Warranty	2 year full warranty		
Certifications and Standard Compliance	USB Interface 2.0 High-Speed, CE, FCC.		