

| | | | |
|---|---|---|------------------------|
| Interface | USB 2.0 high-speed (certified) / with High- and Full-Speed capabilities | | |
| Power Supply | USB bus-powered: | 4.4 – 5.25V | |
| Power Consumption | Suspend Current: | < 500 μ A | |
| | Operating Current: | max. 100 mA | |
| Performance | Read: | up to 8 MB/sec. | Write: up to 3 MB/sec. |
| | <i>Speed depends on used flash modules and may vary.</i> | | |
| Model Code / Size | EAN Code | Size | |
| | 7640111162339 | 1 Gigabyte | |
| | 7640111162346 | 2 Gigabyte | |
| | 7640111162353 | 4 Gigabyte | |
| | 7640111162360 | 8 Gigabyte | |
| | 7640111163091 | 16 Gigabyte | |
| Flash Type | Multi Level Cell (MLC) NAND Flash | | |
| Dimensions (LxWxH) | 71.25 mm x 23.6 mm x 10.2 mm | | |
| Weight | 13 grams | | |
| Operating Systems | Without Driver: | Windows Vista Windows XP Windows 2003 Windows 2000 MAC OS 9 and higher Linux 2.6.x | |
| | With Driver: * | Windows 98SE | |
| | *) <i>downloadable at disk2go.com</i> | | |
| LED Indicator | Rapid blinking: | transferring data | (green LED) |
| | LED on: | connected and inactive | (green LED) |
| Environmental Conditions | Device in operation: | -20 °C to 60 °C | |
| | not in operation/storage: | -40 °C to 80 °C | |
| Service/Warranty | 2 year full warranty | | |
| Certifications and Standard Compliance | CE, FCC, USB IF, RoHS. | | |