



Interface	USB 2.0 high-speed (certified) / with High- and Full-Speed capabilities	
Power Supply	USB bus-powered:	4.4 – 5.25V
Power Consumption	Suspend Current:	< 500 µA
	Operating Current:	max. 100 mA
Performance	Read: up to 8 MB/sec.	Write: up to 3 MB/sec.
	<i>Speed depends on used flash modules and may vary.</i>	
Model Code / Size	EAN Code	Size
	7640111162445	1 Gigabyte
	7640111162452	2 Gigabyte
	7640111162469	4 Gigabyte
	7640111162476	8 Gigabyte
	7640111163107	16 Gigabyte
Flash Type	Multi Level Cell (MLC) NAND Flash	
Dimensions (LxWxH)	71.25 mm x 23.6 mm x 10.2 mm	
Weight	13 grams	
Operating Systems (only USB-Drive)	Without Driver:	Windows Vista Windows XP Windows XP Windows 2000 Windows ME MAC OS 9.0 & higher Linux 2.6.x
	With Driver*:	Windows 98SE *) available at disk2go.com
U3 Applications	<p>U3 applications work under Windows Vista, XP and Windows 2000 SP4 operating systems.</p> <p>On all the other Operating systems previously listed, the U3 smart drive reverts to standard USB data mode, when inserted into the PC or Mac, preserving the user's ability to access the data stored on the drive. U3 smart applications will not run in this case.</p>	
		
LED Indicator	Rapid blinking:	transferring data (green LED)
	LED on:	connected and inactive (green LED)
Software (included)	DmailerSync™ Plus	Advanced data synchronization software
	U-Safe	Password protection
	disk2go® Launchpad	Software Installer
Lost & Found	Service included www.disk2go.com/found	1 year free access
		

Operating Temperature	0°C to +60°C
Storage Temperature	-20°C to +70°C
Environmental Conditions	Device in operation: 0 °C to 60 °C not in operation/storage: -25 °C to 85 °C
Service/Warranty	2 year full warranty
Certifications and Standard Compliance	CE, FCC, USB IF, RoHS.