

Interface	USB 2.0 high-speed / with High- and Full-Speed capabilities		
Power Supply	USB bus-powered:	4.4 – 5.25V	
Power Consumption	Suspend Current:	<500 µA (typical & max)	
	Operating Current:	<100 mA (typical)	<180 mA (max)
Performance	Read:	Min. 5 MB/sec.	
	Write:	Min. 1 MB/sec.	
Model Code / Size	EAN Code	Flash Size	
	836352003785 (blue)	2 GByte	
	836352003792 (green)	2 GByte	
	836352003808 (gray)	2 GByte	
	836352003778 (red)	2 GByte	
Flash Type	Mult Level Cell (MLC) NAND Flash		
Dimensions (LxWxH)	55mm x 16mm x 12mm (UFD device only)		
Weight	5 grams (UFD device only)		
Operating Systems	Without Driver:	Windows Vista Windows XP Windows 2003 Windows 2000 MAC OS X (10.x and higher) Linux 2.6.x	
	With Driver: (available at disk2go.com)	Windows 98SE	
LED Indicator <i>(visibility depends on model)</i>	LED on:	connected and inactive	(red LED)
	Rapid blinking:	transferring/receiving data or engaged in the identification process	(red LED)
Environmental Conditions	Device in operation:	-20 °C to 60 °C	
	not in operation/storage:	-40 °C to 80 °C	
Service/Warranty	2 year full warranty		
Certifications and Standard Compliance	CE, FCC, USB IF, RoHS.		