

Interface	USB 2.0 high-speed (certified) / with High- and Full-Speed capabilities	
Power Supply	USB bus-powered:	4.4 – 5.25V
Power Consumption	Suspend Current:	500 mA (max)
	Operating Current:	21mA (max)
Performance	Read:	8 MB/sec.
	Write:	7 MB/sec.
EAN Code/Capacity	7640111160892	128 Megabyte
	7640111160908	256 Megabyte
	7640111160915	512 Megabyte
	7640111160922	1 Gigabyte
	7640111161295	2 Gigabyte
	7640111162391	4 Gigabyte
Dimensions (LxWxH)	49.0 x 19.5 x 3.5 mm	
Weight	8 gram (0.28 ounces)	
Operating Systems	Without Driver:	Windows Vista Windows XP Windows 2000 Windows ME MAC OS 9.0 Linux 2.6
	With Driver: (available at disk2go.com)	Windows 98SE
Operating Temperature	+10°C to + 60°C +50°F to +140°F	
Storage Temperature	-20°C to + 80°C -4°F to +176°F	
Service/Warranty	2 year full warranty	
EMI Compliance	USB Interface 2.0 MIC, CE, FCC	
	USB Interface 2.0, Full Speed, WHQL für Windows XP, 2000 and ME, CE and FCC, TÜV, UL and CB, EN 55022 (CE), AS/NZS 3548 (Australia and New Zealand Standard), CISPR 22 (VCCI Japan and MIC Korea), BSMI CNS 13438 (Taiwan Inspection Standard), CFR 47 FCC (FCC), EN 55024 (CE and MIC Korea)	